


**NOTES:**

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
- ② GLASS THICKNESS: 4.0mm NOMINAL.
- ③ TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. GLASS IS BEVELED UNDER TRANSDUCERS. HEIGHT OF TRANSDUCERS BELOW GLASS.
- ④ CABLE ROUTING ADDS A MAXIMUM OF 2.5mm AS INDICATED ON THE SCREEN. CABLE IS ROUTED ALONG THE BEVEL.
- ⑤ LINE 14-6CX-XXX. WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
  - SAW SERIAL CONTROL BOARD SAW232(6000S)
  - SAW USB CONTROL BOARD SAWUSB (6000U)
6. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	VEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

							MODEL	SAW1700-KR	PROJECTION	
							DESCRIPTION	17"	SIZE:	A4
							MATERIAL		WEIGHT:	Kg
							FINISH		COLOR:	
A	FIRST ISSUE	13-11-13	Beacher	BING	CLOUD	DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: XX=±1.0 .XX=±0.5 ANGULAR TOL: ±1°				
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1		REV. A	